

Sail Measurement Form National Letters and Sail Numbers

CVII	NUMBER:		
SAII	NUMBER.		

	Dimension no				
ITEM	[as per rule 6.5.1]	MEASUREMENT	Min. (mm)	Actual (mm)	Max. (mm)
1	1	Height	230	All OK / Not OK	240
2	2	Width (except "1" or "I")	150	All OK / Not OK	160
3	3	Width for M and W	160	All OK / Not OK	170
4	4	Thickness	30	All OK / Not OK	40
5	5	Space between adjoining numbers or letters	40	All OK / Not OK	50
6	6	Space between rows of numbers or letters	40	All OK / Not OK	50
7	7	Space between the national letter groups on opposite sides of the sail	100		150
8	8	Distance between the luff and the closest letter or number in each row	150		
9	9	Distance between lower edge of uppermost batten pocket and the national letter which is closest to the leech	40		50
10	RRS G1.2(b)	Minimum space between characters and edge of sail (leech)	45	All OK / Not OK	

Measurer's Name IN BLOCK CAPITALS:					
Measurer's signature:	Date: Measurer recognised by:				
Second Measurement If the sail letters/number is changed					
SAIL NUMBER:					
Owner's Name:					

	Dimension no				
ITEM	[as per rule 6.5.1]	MEASUREMENT	Min. (mm)	Actual (mm)	Max. (mm)
1	1	Height	230	All OK / Not OK	240
2	2	Width (except "1" or "I")	150	All OK / Not OK	160
3	3	Width for M and W	160	All OK / Not OK	170
4	4	Thickness	30	All OK / Not OK	40
5	5	Space between adjoining numbers or letters	40	All OK / Not OK	50
6	6	Space between rows of numbers or letters	40	All OK / Not OK	50
7	7	Space between the national letter groups on opposite sides of the sail	100		150
8	8	Distance between the luff and the closest letter or number in each row	150		
9	9	Distance between lower edge of uppermost batten pocket and the national letter which is closest to the leech	40		50
10	RRS G1.2(b)	Minimum space between characters and edge of sail (leech)	45	All OK / Not OK	

Measurer's Name IN BLOCK CAPITALS:		
Measurer's signature:	_ Date:	Measurer recognised by: